

## 4500KG COMPACT SHORT JIB

### FJA-19-451

The 4500kg compact short jib is designed to give increased lift height as the jibs profile is low. This is a general-purpose jib able to manoeuvre in confined spaces, with a 1.90m reach when fully extended. Simply drive your fork tines through the pockets and secure the safety chain to the carriage. The jibs overall length when closed is 1.25m. This comes in a galvanised finish and includes a manual/certificate, safety chain and swivel hook.

#### Specifications;

- Safe Working Load 4500kg
- Pocket Size 185 x 65mm
- Pocket Centres 290mm
- Load Centre 670mm
- Horizontal C of G 735mm
- Vertical C of G 120mm
- Unit Weight 95kg
- Manufactured strictly in accordance with AS 2359.1



Detail	Safe Working Load (SWL) Per Position			
	1	2	3	4
Position	1	2	3	4
Extension (mm)	670	1165	1545	1925
SWL (kg)	4500	2900	1300	750

## 4500KG COMPACT LONG JIB

### FJA-19-456

Versatile and very economical with a 3.50m reach when fully extended, this jib is ideal for long loads to be carried. As the jib profile is low, your load can be lifted into tight spots near ceilings or under racking beams. This slip-on forklift attachment is held to the forklift by the safety chain. The jibs overall length when closed is 2.03m and has 6 lifting points from 870mm to 3465mm. This comes in a galvanised finish and includes a manual/certificate, safety chain and swivel hook.

#### Specifications;

- Safe Working Load 4500kg
- Pocket Size 185 x 65mm
- Pocket Centres 290mm
- Load Centre 870mm
- Horizontal C of G 1295mm
- Vertical C of G 125mm
- Unit Weight 140kg
- Manufactured strictly in accordance with AS 2359.1

Detail	Safe Working Load (SWL) Per Position					
	1	2	3	4	5	6
Position	1	2	3	4	5	6
Extension (mm)	870	1945	2325	2705	3085	3465
SWL (kg)	4500	1300	750	560	380	200

