

Adjustable Spreader Beam

The FSB-09-240 Adjustable Spreader Beam is a unique multi-tasking beam which is designed to lift long loads via the centre single hook point as a 'Lifting Beam', or end lifted using a 2-leg chain sling as a 'Spreader Beam' with an overhead crane or forklift.

Specifications

Type:	Rated Capacity:				Fork Pocket		Unit Weight: (kg)
	Used as a:	Fully retracted: (LC@2405mm)	Middle position: (LC@3165mm)	Fully extended: (LC@3925mm)	Size: (mm)	Centre: (mm)	
FSB-09-240	Forklift attachment	5600kg	2900kg	1400kg	185 x 85	900	260
	Lifting Beam	6000kg	4500kg	2400kg			
	Spreader Beam	10,000kg	10,000 kg	10,000kg			

Features

- > Can be lifted by Forklift or Crane
- > Load connection points are adjustable to 3 positions by moving the extendable arm in position
- > The 600mm long slipper pockets allow fast and safe connection to the truck
- > Safety pins included, used to securely lock extendable arm in position
- > Fitted with 2 safety swivel hooks
- > Zinc finish on extendable arms, enamel paint finish on main body
- > Certified to relevant AS Standards



4 Harbour Ridge Drive, Manukau City PO Box 97410, Manukau City 2241

Tel: 09 263 7725 Fax: 09 262 0970 Email: sales@stratalign.co.nz

GANTRY CRANES, CHAIN HOISTS, ELECTRIC HOISTS, SLINGS, LEVER HOISTS, MAGNETIC CLAMPS