

MAN CAGE EXTENSION RISER

The riser is used in conjunction with the standard forklift man cage and is primarily used in areas where extra lift height is required for maintenance work.

Features;

- Available in varying heights up to 1600mm
- Certified to NZ Standards
- Platform at the top of the riser for safe entry/exit of man cage
- Painted safety yellow finish



SAFETY HARNESS & LANYARD

FMC-19-121

Our standard Full Body Harness features two attachment webbing loops and a dorsal attachment D-Ring for fall arrest. The sternal attachment points are particularly suitable for use with rope or cable grabs and offer a comfortable position to work from as well as for rescue. High strength, easy adjustment webbing buckles are used on both legs and chest. Other features include easy-grip shoulder adjustment buckles, webbing fall arrest loops and high strength stitch pattern. Webbing shock absorbing lanyards with 2 double action hooks are made from the highest quality polyester webbing with synthetic stitching. Ideal for General Use, Construction or Mobile Platform use. A tear-out section is employed to reduce the forces and limit the effect on a user in a fall below 600KN. Supplied in Heavy Duty PVC Tog Bag for extra convenience. General purpose harness with front and rear 'D'; attachment points. Fully adjustable with quick release buckles for ease of use.

Specifications;

- Webbing lanyard with snap hooks at both ends
- Includes shock absorber
- Conforms to EN 355
- Lanyard Length: 2m
- Material: Polyamide 100%
- Manufactured strictly in accordance with AS/NZS 1891.4

