## **SPRING BALANCERS**

## 1.5KG - 200KG

- Suitable for single continuous operation on the production line for suspending, concentrating, handling and moving or removing tools, clamps, clips and frames etc.
- Installed with high quality coil spring.
- Fall prevention device and drum lock to ensure a high level of safety.
- Reduces fatigue and improves operation efficiency.
- Complies with requirements of the EU Machinery Directive 98/37 /EC. They also comply with European standards EN 1050: 1997, EN 12100-1 :2003, EN 12100-2:2003.
- Non-coated Aluminium Spring Balancers are also available complete with stainless steel wire designed for the food industry.

Model	Capacity (kg)	Length (m)	Net Weight (kg)
SBPH-1-5/3-0	1.5-3	2.0	2.0
SBPH-3-0/5-0	3-5	1.3	1.3
SBPH-4-5/9-0	4.5-9	1.3	3.4
SBPH-9-0/15-0	9-15	1.5	3.8
SBPH-15-0/22-0	15-22	1.5	7.2
SBPH-22-0/30-0	22-30	1.5	7.6
SBPH-30-0/40-0	30-40	1.5	9.8
SBPH-40-0/50-0	40-50	1.5	10.4
SBPH-50-0/60-0	50-60	1.5	11.6
SBPH-60-0/70-0	60-70	1.5	11.8
SBPH-70-0/80-0	40-80	1.5	18.0
SBPH-58-0/105-0	85-105	1.5	18.6
SBPH-100-0/120-0	100-120	1.5	19.8
SBPH-120-0/140-0	120-140	1.5	20.6
SBPH-140-0/160-0	140-160	1.5	22.0
SBPH-160-0/180-0	160-180	1.5	26.0
SBPH-180-0/200-0	180-200	1.5	28.0





















